ThermaGuard, ?????? ????????? ?????????? ??????? - ?????????

ThermaGuard, ?????? ????????? ?????????? ??????? - ?????????. ??? ????????? ??????? - ?? ???? (101) ? ?? ??? (102) ??????????? ??????????. ?????? ?? ????????? ??????? EN 13485. ?????????????????? ?????????? ?????????? ?????? ??? ??????? ????????????? ?????????? ??? ???????? / ????????? ????????????. ?????: ?????????? ?????????? -39.9 to 49.9 °C, ?????????? -19.9 to 49.9 °C (101 model only). ??????? ??? ????????????? ?????. ??????? ?? ???????????. Made In England

??????????: ??? ???????????? ?????
????
???? ?? ??????? 127,92 €

???? ??????? 158,62 €

???? ??????? ????? ???? 127,92 €

???????

???????? ????? 30,70 €

??????? ??? ?? ??????

?????????

ThermaGuard, ?????? ????????? ?????????? ??????? - ?????????

Made In England

??????? ?? ???????????.

??? ????????? ??????? - ?? ???? (101) ? ?? ??? (102) ??????????? ??????????.
?????? ?? ????????? ??????? EN 13485.

?????: ?????????? ?????????? -39.9 to 49.9 °C, ?????????? -19.9 to 49.9 °C (101 model only)

??? ?? ??? ??????? ????????? ?????????????????? ????????? ??????????? ??? ?????????? ??? ?????? ?? ??????????? ?? ???? ?????? ??? ??????? ???????????. ???? ? ?????????? ????? ???????, ? ????? LCD ?? ???????????. ? ?????????? ?????? ?? ??????? ???????? ??????????? ??????.

??????? ??? ????????????? ?????.

Each ThermaGuard is housed in a splashproof IP54, ABS case which includes the 'Biomaster' additive that reduces bacterial growth, ideal for monitoring chilled and frozen foods.
An optional two-point (-18, 0°C) UKAS Certificate of Calibration is available. Each certificate indicates deviations from standards at -18 and 0 °C. *UKAS certificate applies to remote probes only
two models available
The ThermaGuard 101 incorporates two temperature sensors; a remote water resistant probe with a one metre PVC lead for monitoring the appliance temperature and an internal sensor for the room temperature. The ThermaGuard 102 incorporates two remote water resistant probes, both with one metre PVC leads for monitoring two appliances. Each remote probe can be mounted onto the internal wall of the fridge using the small ABS plastic mounting bracket supplied.
CalCheck function
Both models of the ThermaGuard features a CalCheck 0.0 °C (±0.1 °C) function that allows the user to verify the accuracy of the thermometer at any time, giving confidence that measurements are accurate.
Free wall bracket
Each ThermaGuard is supplied with a plastic wall bracket that incorporates a built-in foot stand, hook for hanging and screw thread for tripod mounting, allowing users to store or position the unit safely, securely and protect against accidental damage.

range internal:	-19.9 to 49.9 °C (101 model only)
range external:	-39.9 to 49.9 °C
resolution:	0.1 °C/°F
accuracy:	±0.4 °C
battery:	2 x 1.5 volt AA
battery life:	25000 hours (normal use, without alarm)
sensor type:	thermistor
display:	custom LCD
dimensions:	29 x 73 x 96 mm
weight:	165 grams
country of manufacture:	United Kingdom
guarantee:	two years
certification:	optional UKAS Certificate of Calibration available
conforms to standard:	EN 13485