

???????????? ????????, ThermaGuard Pharm



?????????? ????????, ThermaGuard Pharm. ?????????? ThermaGuard® Pharm ??? ?????????????? ?? ?????????? ?? ?????????????? ??
?????????? ?? ?? ??????????. ??????? ?? ?????????????? ??????. ?????????? ?????????? ?????????????? ?? ?????????????? ??
????????????? ?? ??????????. ?? ?????????? ????????? - ????? ? ?? ?????????? ??????????. ?????? ?? ?????????? ??????? EN 13485.
????????????????????? ?????????? ?????? & ?????? ??????????????. ?????? ?? ??????????????.

?????????: ?? ?????????????? ??????

????

??? ?? ?????? 141,96 €

??? ?????? 176,03 €

??? ?????? ?????? ??? 141,96 €

??????

????????? ?????? 34,07 €

[?????? ?? ?? ??????](#)

?????????

?????????? ????????, ThermaGuard Pharm.

?????? ?? ??????????

?????????? ThermaGuard® Pharm ??? ?????????????? ?? ?????????? ?? ?????????????? ?? ?????????? ?? ?? ??????????.

????????? ?? ?????????????? ??????.

?? ThermaGuard Pharm ??? ?????????? ?????? ?? ?????? ?? ?????????????? ?? ?????????????? ?????????????? ?? ?????????? ??????

????????????, ??? ??????, ?????? ?? ??????. ??? ?????????? ??????? ?? ?????? ????? LCD, ? ??? ?????????? ?????????? ?????????? ?? ?????????? / ?????????? ?????????????????? ?????????????.

Both units feature programmable audible alarms allowing the user to preset high and low temperature limits. When the alarm is active the LCD will flash. The alarm can be silenced by pressing any button.

Housed in a splash-proof IP54 ABS case, which includes the 'Biomaster' additive that reduces bacterial growth, both ThermaGuard Pharm models feature a CalCheck 0.0 °C (±0.1 °C) function that allows the user to verify the accuracy of the thermometer at any time, giving confidence that measurements are accurate.

Each thermistor probe is encased in a sealed bottle. To begin monitoring, simply unscrew and top up with Glycol solution (50 ml bottle supplied).

two models available
The ThermaGuard Pharm 101 incorporates two temperature sensors; a remote water resistant thermistor probe with a one metre PVC lead for monitoring the product temperature and an internal sensor to monitor room temperature. The ThermaGuard 102 incorporates two remote water resistant thermistor probes, both with one metre PVC leads for monitoring dual applications. An optional two-point UKAS Certificate of Calibration is available. Each certificate indicates deviations from standards at -18 and 0 °C. All ThermaGuard Pharm models come with 2000 mm cable lengths

CalCheck function
Both models of the ThermaGuard features a CalCheck 0.0 °C (±0.1 °C) function that allows the user to verify the accuracy of the thermometer at any time, giving confidence that measurements are accurate.

Free wall bracket
Each ThermaGuard Pharm is supplied with a plastic wall bracket that incorporates a built-in foot stand, hook for hanging and screw thread for tripod mounting, allowing users to store or position the unit safely, securely and protect against accidental damage.

????????????

range internal:	-19.9 to 49.9 °C (101 model only)
range external:	-39.9 to 49.9 °C
resolution:	0.1 °C/°F
accuracy:	±0.4 °C
battery:	2 x 1.5 volt AA
battery life:	25000 hours (normal use, without alarm)
sensor type:	thermistor
display:	custom LCD
dimensions:	29 x 73 x 96 mm
weight:	165 grams
country of manufacture:	United Kingdom
guarantee:	two years
certification:	optional UKAS Certificate of Calibration available
conforms to standard:	EN 13485